

ENGEL

SINCE 1962

A LEGEND IN RELIABILITY®



ENGINE

MODEL	R5500iE
TYPE	R300 25° Singel cylinder, 4 stroke air-cooled cylinder centre inclined.
DISPLACEMENT	301cc
STARTING SYSTEM	Recoil & Electric Starter
STOPPING SYSTEM	Ignition Primary Circuit Starter
IGNITION SYSTEM	Transistorized Magneto
FUEL TYPE	Unleaded
FUEL CAPACITY (LTRS)	16L
FUEL CONSUMPTION	<450g/kW.h
CONTINUOUS RUNNING TIMES	Full Load = 5hrs Half Load = 9hrs Quarter Load = 16hrs
OIL ALERT	Yes
NOISE (At 7m)	74dBA

GENERATOR

RATED POWER OUTPUT (KVA)	5KVA
MAX POWER OUTPUT (KVA)	5.5KVA
RATED OUTPUT FREQUENCY	50Hz
RATED OUTPUT VOLTAGE	240v
D.C. OUTPUT	External Terminals
A.C. OUTPUT	240v 50Hz
BATTERY CHARGING	Yes
FREQUENCY METER	Yes
VOLTMETER	Yes
RATED VOLTAGE	240v
RATED FREQUENCY	50Hz
FUEL GUAGE	Yes
AC CIRCUIT BREAKER	Yes
AUTO THROTTLE	Eco Throttle
AIR CLEANER	Foam Type
PARALLEL OPERATIONS CONNECTION PORTS	Yes
PARALLEL OPERATIONS CONNECTION CABLE	Optional
TWO WHEEL & HANDLE KIT	Yes
LIFETIME	500HRS
DIMENSIONS (mm)	598mm(H) - 643mm(W) - 643mm(D)
WEIGHT	60kg
PACKING	Carton
PACKING SIZE	TBA
TOOL KIT	Various Spanners & Tools

ENGEL R5500iE

Engel Distrubution Pty Ltd



P.O.Box 155 Ellen Grove, Qld 4300



orders@engelaustralia.com.au



1300 436 435

\$1999.00

RRP inc GST